

Education Partners Solution, Inc. 3506 Hwy 6 S., Suite 226 Sugar Land, TX 77478-4401 Voice: (281) 494-0187

FAX: (281) 980-2942 Email: gifford@eps4.com

November 22, 2000

CBISD CABLE RFQ ADDENDUM #2

This addendum documents the questions, answers and statements following the CBISD CABLE RFQ Addendum #1 release.

1. Building Interconnect

- a) Q: If the conduit between the new high school and the administration building is not available, is <u>it required that the vendor run underground?</u> A: Underground is preferred. We will review add alternate submissions for the most cost effective, efficient and esthetically pleasing route.
- b) Q: Of the four 1-1/4" conduits installed, how many are being used and how many are open? A: Two used, one with 12-strand multimode and one with 50 pair voice tie cable (reference addendum #1).
 - i) One 1 1/4 buried conduit currently contains a 50 pair voice tie cable from the Administration MC to the "F" building IC.
 - ii) One 1 1/4 buried conduit currently contains a 12 strand multimode fiber optic tie cable from the Administration MC to the "F" building IC.
- c) Q: If the existing conduit is not sufficient, will the vendor be responsible for installing additional conduit? A: Yes, if the vendor determines adequate conduit space is not available, the vendor will add conduit route to support the physical cable demand. Please price separately.

2. Documentation

a) <u>Q: Are there AutoCAD files available for "D" and "G" buildings?</u> A: No, but I have posted my building and drawing notes at http://www.eps4.com/bldnotes.PDF.

3. Speaker components

- a) Q: What are the speaker specifications?
 - Speakers are not a part of this RFQ but part of the Telephone RFQ. These specifications will be finalized when the Telephone RFQ is awarded.
 - ii) There will be a total of twelve (12) runs from the associated building IC to key hallway interchanges that will be made available to the Telephone contractor.
 - iii) Please provide reference to similar jobs.

4. CATV

a) <u>Q: What are the CATV Headend specifications?</u> A: Provide a minimum 750 MHz or 850 MHz, as per the RFQ, distribution system with distribution amplifier. Materials will be Blonder-Tongue Laboratories, Inc. or equivalent as specified in Section 5.